

YSI Profe



The Quatro cable bulkhead shown with four user-replaceable sensors including temperature/conductivity, DO, pH, and ammonium.



YSI Professional Plus Quatro Cable

The Quatro Cable with the Pro Plus Provides the Ultimate Handheld Multiparameter Instrument

The Quatro is a new 4-port cable and bulkhead for the Professional Plus handheld instrument making it possible to measure conductivity and temperature, dissolved oxygen, and your choice of any two ISE's among pH, ORP, ammonium, nitrate or chloride.

All sensors are rugged and designed for true field work to reduce the overall cost of ownership.

- Holds four user replaceable Professional Series sensors for temperature/conductivity, dissolved oxygen and a choice of any two ISE's among pH, ORP, ammonium, nitrate or chloride.
- Rugged and waterproof Military Spec (MS) connectors to connect to the Professional Plus instrument.
- Choose either polarographic or galvanic DO sensors.
- Weighted guard ensures correct depth while protecting the sensors.
- 2-year cable warranty
- Choose among 1-, 4-, 10-, 20- and 30-meter cable lengths.
- Cable management kit included on any cable 4-meters or longer.

The Professional Plus with the Quatro 4-port cable enables you to conveniently sample an entire suite of parameters and easily download that data into the Data Manager desktop software.

As always, the Pro Plus comes with the communications saddle, USB cable, and Data Manager. By adding the Quatro, you can create a one-of-a-kind handheld multiparameter instrument.

To learn more about the Pro Plus visit www.ysi.com/proplus.



+1 937 767 7241 800 897 4151 (US) www.ysi.com

YSI Environmental +1 937 767 7241 Fax +1 937 767 9353 environmental@ysi.com

YSI Integrated Systems +1 508 748 0366 systems@ysi.com

SonTek/YSI +1 858 546 8327 inquiry@sontek.com

YSI Gulf Coast +1 225 753 2650 environmental@ysi.com

AMJ Environmental +1 877 392 9950 amj@ysi.com

YSI Hydrodata (UK) +44 1462 673 581 europe@ysi.com

YSI Middle East (Bahrain) +973 1753 6222 halsalem@ysi.com

YSI (Hong Kong) Limited +852 2891 8154 hongkong@ysi.com

YSI (China) Limited +86 532 575 3636 beijing@ysi-china.com

YSI Nanotech (Japan) +81 44 222 0009 nanotech@ysi.com

YSI Australia +61 7 390 17233 acorbett@ysi.com

YSI India +91 989 122 0639 sham@ysi.com



Pure Data for a Healthy Planet and Who's Minding the Planet? are registered trademarks of YSI Incorporated.

©2008 YSI Incorporated

Printed in the USA 1208 W4-01



Y S I incorporated
Who's Minding
the Planet?™

Quatro Cable Specifications

 Weight (1-meter cable with sensors)
 525 grams (1.15 lbs)

 Diameter
 4.70 cm (1.85 in)

 Probe Guard Length
 12.65 cm (4.98 in)

Connector Military spec (MS), waterproof, bayonet lock

Quatro Ordering Information

605790-1 1-m cable with 4-ports and 5560 temp/conductivity sensor
605790-4* 4-m cable with 4-ports and 5560 temp/conductivity sensor
605790-10* 10-m cable with 4-ports and 5560 temp/conductivity sensor
605790-20* 20-m cable with 4-ports and 5560 temp/conductivity sensor
605790-30* 30-m cable with 4-ports and 5560 temp/conductivity sensor
6050000 Professional Plus instrument (the Quatro can only be used with the Professional Plus)

605202 Galvanic dissolved oxygen sensor 605203 Polarographic dissolved oxygen sensor

605101 pH sensor 605102 ORP sensor

calibration solutions.

5909

605104** Ammonium ISE, NH4+ sensor (17-meter maximum depth)

605105** Chloride ISE sensor (17-meter maximum depth) 605106** Nitrate ISE sensor (17-meter maximum depth)

Accessories Ordering Information

5913***
 1.25 mil PE membranes for galvanic (6 yellow caps/solution)
 5908***
 1.25 mil PE membranes for polarographic (6 yellow caps/solution)
 2 mil PE membranes for galvanic (6 blue caps/solution)

2 mil PE membranes for polarographic (6 blue caps/solution)

Please visit www.ysi.com/accessories for a full line of Professional Series accessories and

* Includes cable management kit. ** Freshwater only. *** Standard membranes.

The waterproof, military spec connector is designed for true field performance. All YSI cables are designed for rugged field use.



Four ports for user-replaceable sensors. Ports accept a temperature/ conductivity combo sensor, DO sensor, and any combination of two ISE sensors among pH, ORP, ammonium, chloride, or nitrate. If a port isn't used simply put a port plug in it's place.



A cable management kit is included with all cables 4-meters and over. Conveniently, manage your longer cable lengths. Also easily attaches to the outside of the soft-sided carrying case instead of placing wet, dirty cables inside.



All user-replaceable sensors feature a double o-ring creating a waterproof connection and enabling the sensors to be used at depths up to 30-meters.



A rugged, weighted probe guard protects the sensors and ensures the correct depths on longer cables